


## R1210

### ROOF DRAIN CAST IRON BODY WITH 12" CAST IRON-DOME



**PRODUCT SPECIFICATION:** 12" [305mm] Diameter roof drain, Dura-Coated cast iron body with combination membrane flashing clamp/gravel guard and cast-iron dome

A Pipe Size In.[mm]	Approx. Wt. Lbs. [kg]	Dome Open Area Sq. In. [cm <sup>2</sup> ]
2,3,4,6 [51, 76, 102, 152]	22 [10]	78 [503]

PIPE SIZE	(Specify size/type) OUTLET	'E' BODY HT. DIM.
2, 3, 4, 6 [51, 76, 102, 152]	_C Inside Caulk	5-1/4 [133]
2, 3, 4, 6 [51, 76, 102, 152]	_P Threaded	3-3/4 [95]
2, 3, 4, 6 [51, 76, 102, 152]	_NH No-Hub	5-1/4 [133]
2, 3, 4 [51, 76, 102]	_NL Neo-Loc	4-5/8 [117]

#### PREFIXES

**RC** - Cast Iron body Assembly Cast Iron Dome\*

**RA** - Cast Iron body Assembly Aluminium Dome

**RP** - Cast Iron body Assembly Poly Dome

#### SUFFIXES

- **AR** Acid Resistant Epoxy Coated Cast Iron
- **C** Underdeck Clamp
- **DP** Top-Set® Roof Deck Plate
- **E** 2 [51] High Static Extension (Specify Height)
- **EB** Top-Set® Adjustable Extension Assembly
- **FG** Flush Grate (Replaces Dome Strainer)
- **G** Galvanized Cast Iron
- **R** Roof Sump Receiver
- **SC** Secondary Clamping Collar
- **SS** Stainless Mesh Screen Over Dome
- **TC** Neo-Loc Test Cap Gasket
- (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only)
- **VP** Vandal-Proof Secured Top
- **XJ** Vertical Expansion Joint
- **84** Stainless Steel Perforated Gravel Guard
- **85** Stainless Steel Perforated Extension
- **89** 2 [51] High External Water Dam
- **90** 90° Threaded Side Outlet Body