


R1250

ROOF DRAIN CAST IRON BODY WITH 8" CAST IRON-DOME



PRODUCT SPECIFICATION: 8-3/8" [213mm] Diameter roof drain, Dura-Coated cast iron body with combination membrane flashing clamp/gravel guard and cast iron dome

A Pipe Size In. [mm]	Approx. Wt. Lbs. [kg]	Dome Open Area Sq. In. [cm ²]
2, 3, 4 [51, 76, 102]	14 [6]	43 [277]

PIPE SIZE	(Specify size/type) OUTLET	'E' BODY HT. DIM.
2, 3, 4 [51, 76, 102]	_C Inside Caulk	3-7/8 [98]
2 [51]	_P Threaded	2-7/16 [62]
3 [76]	_P Threaded	2-3/4 [70]
4 [102]	_P Threaded	3 [76]
2, 3, 4 [51, 76, 102]	_NH No-Hub	4 [102]
2, 3, 4 [51, 76, 102]	_NL Neo-Loc	3-13/16 [97]

PREFIXES

RC - Cast Iron body Assembly Cast Iron Dome*

RA - Cast Iron body Assembly Aluminium Dome

RP - Cast Iron body Assembly Poly Dome

SUFFIXES

- **AR** Acid Resistant Epoxy Coated Cast Iron
- **C** Underdeck Clamp
- **DP** Top-Set® Roof Deck Plate
- **E** 2 [51] High Static Extension (Specify Height)
- **EB** Top-Set® Adjustable Extension Assembly
- **FG** Flush Grate (Replaces Dome Strainer)
- **G** Galvanized Cast Iron
- **R** Roof Sump Receiver
- **SC** Secondary Clamping Collar
- **SS** Stainless Mesh Screen Over Dome
- **TC** Neo-Loc Test Cap Gasket
- (2, 3, 4 [51, 76, 102] NL Bottom Outlet Only)
- **VP** Vandal-Proof Secured Top
- **XJ** Vertical Expansion Joint
- **84** Stainless Steel Perforated Gravel Guard
- **85** Stainless Steel Perforated Extension
- **89** 2 [51] High External Water Dam
- **90** 90° Threaded Side Outlet Body