


R4150B

CAST IRON BODY WITH ROUND STRAINER



PRODUCT SPECIFICATION: Floor drain, Epoxy Coated cast iron body with membrane clamp and adjustable collar, Round polished nickel bronze strainer

Dimensions in Inches [mm]						Approx. Wt. Lbs. [kg]	Strainer Open Area Sq. In. [cm²]
A - Pipe Size	B Strainer Size	K		K'			
		Min.	Max.	Min.	Max.		
2,3 [51,76]	5 [127]	1 [25]	1-1/2 [38]	1-3/32 [28]	2-1/4 [57]	11 [5]	6-1/4 [40]
2,3,4 [51,76,102]	6 [152]	1 [25]	1-25/32 [45]	1-13/32 [36]	2-17/32 [64]	13 [6]	9 [58]
2,3,4 [51,76,102]	7 [178]	1 [25]	2-1/8 [54]	1-23/32 [44]	2-7/8 [73]	14 [6]	12 [77]
3,4 [76,102]	8 [203]	1-5/32 [30]	2-1/8 [54]	1-3/4 [44]	2-7/8 [73]	16 [7]	19 [123]
6 [152]	8 [203]	1-5/32 [30]	2-1/8 [54]	1-3/4 [44]	2-7/8 [73]	18 [8]	19 [123]
6 [152]	10 [254]	1-7/16 [37]	2-1/2 [64]	2 [51]	3-1/4 [83]	22 [10]	23 [148]

PIPE SIZE

2,3,4 [51,76,102]
2 [51]
3 [76]
4 [102]
6 [152]
2,3,4 [51,76,102]
2,3,4 [51,76,102]

OUTLET TYPE

_C Inside Caulk
_P Threaded
_P Threaded
_P Threaded
_P Threaded
_NH No-Hub
_G Inside Gasket

BODY HT ('E')

4-3/16 [106]
2-7/16 [62]
2-3/4 [70]
2-13/16 [71]
2-7/8 [73]
3-13/16 [97]
4-3/16 [106]

PREFIXES

RB - Cast Iron body Assembly with Polished Bronze Strainer

RN - Cast Iron body Assembly with Polished Nickel Bronze Strainer*

RS - Cast Iron body Assembly with SS304 Strainer

SUFFIXES

- **AR** Acid Resistant Epoxy Coated Cast Iron
- **C** Chrome Plated Bronze Top
- **G** Galvanized Cast Iron
- **VP** Vandal-Proof Secured Top
- **Y** Sediment Bucket
- **P** Trap Primer Connection